

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES 20

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problems Mailbox.**

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H04L 12/56		A1	(11) International Publication Number: WO 99/05829
			(43) International Publication Date: 4 February 1999 (04.02.99)
(21) International Application Number: PCT/US98/15345			(81) Designated States: AL, AU, BA, BB, BG, BR, CA, CN, CU, CZ, EE, GE, HU, ID, IL, IS, JP, KP, KR, LC, LK, LR, LT, LV, MG, MK, MN, MX, NO, NZ, PL, RO, SG, SI, SK, SL, TR, TT, UA, UZ, VN, YU, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).
(22) International Filing Date: 23 July 1998 (23.07.98)			
(30) Priority Data: 08/899,782 25 July 1997 (25.07.97) US			
(71) Applicant: MASSACHUSETTS INSTITUTE OF TECHNOLOGY [US/US]; 77 Massachusetts Avenue, Cambridge, MA 02139 (US).			
(72) Inventor: POOR, Robert; Apartment 201, 218 Thorndike Street, Cambridge, MA 02141 (US).			
(74) Agents: CESARI, Robert, A. et al.; Cesari and McKenna, LLP, 30 Rowes Wharf, Boston, MA 02110 (US).			


Published

With international search report.

(54) Title: COST BASED ROUTING PROTOCOL

(57) Abstract

A wireless network in which each message transmitted by a node is received by all the neighboring nodes. Each node maintains a table containing entries specifying the cost of transmission from that node to each of the other nodes in the network. Each message frame includes a field containing the remaining cost of transmission of the frame to the destination node for the message. When a node receives a message frame for which it is not the destination it compares the remaining cost with the cost contained in the table entry for the destination node. If the table entry cost is less than the remaining cost, the node decrements the remaining cost and retransmits the frame. Otherwise it discards the frame.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

COST BASED ROUTING PROTOCOL

BACKGROUND OF THE INVENTION

This invention relates to a self-organizing, wireless digital network. More specifically, it relates to a wireless network in which each node communicates directly only with neighboring nodes, the latter nodes relaying transmissions to more distant
5 nodes. In one application of the invention, each node has a low-power transmitter and its neighboring nodes are only a few meters distant.

In one aspect the invention is directed at networks comprising a large number of nodes in relatively close proximity to each other. A typical application is an office environment in which a number of workstations and servers are linked in a local area
10 network (LAN). Conventionally, these nodes are interconnected by cables, usually through a central hub. Installation of the cables is a material element of cost in these networks. Moreover, cabled networks are relatively inflexible in that a node usually cannot be moved from one location to another without installing a new cable. Furthermore, it is particularly expensive to install cables in completed structures, since
15 they cannot be hidden from sight without "fishing" them through the spaces between walls or, in some cases, opening up the walls to gain access to the interiors.

The foregoing problems have been overcome in part by resort to wireless LANs, which replicate the conventional wired arrangements, e.g. ethernet and token ring, but without the use of cables. Each of the nodes includes a wireless transceiver
20 which communicates with other nodes in the network by means of radio frequency signals. These networks eliminate the installation costs associated with wired networks and, furthermore, they provide substantially more flexibility with regard to location and relocation of the respective network nodes. Even so, the cost of these wireless networks is too high for some applications. For example, one might wish to use a net-
25 work to interconnect large numbers of low-cost devices such as simple condition sensors and controllers and, in that case, the network interface of each node might well exceed the cost of the device. This problem would be even more acute in a home envi-

ronment where the cost cannot be justified by possible savings that might be obtained in a commercial environment.

There are other arrangements which can be applied to wireless networks and, particularly, to networks that employ very short-range, and therefore low-cost transceivers. These are ad-hoc routing systems which generally fall under the category of
5 "Link State Routing" and "Source Path Routing".

In Link State Routing each node maintains a routing table that specifies an "optimal" path toward each network destination. The meaning of "optimal" is generally interpreted to mean the shortest path, but may account for other factors such as
10 load balancing.

When a node in a Link State Routing system is to transmit a message to a destination node, it first fetches from a routing table an entry for the specified destination. The routing table entry specifies which neighbor of the originating node should relay the message and the identification of that neighbor is installed in the message header as
15 the recipient. The originating node then broadcasts the message. Of all the neighbors that receive the broadcast, only the specified recipient acts on the message, relaying the message in the same manner, according to the entry in its routing table corresponding to the destination node. This process continues until the message reaches the ultimate destination.

20 In Source Path Routing, the originating node enters the entire route of the message into the message header, identifying each node through which the message should be relayed in order to reach the destination node. If a receiving node is not the last named node in the message's source route, it simply relays the message to the next node on the route.

25 Both Link State Routing and Source Path Routing require that each node in the network keep a constant record of its neighboring nodes and, furthermore, that it broadcast any changes in its list of neighboring nodes. This requires that each node send periodic messages to each of its neighbors. All of these messages are generally undesirable since they consume power and system bandwidth. Moreover, they may

facilitate the ability of eavesdroppers to ascertain system information, including the locations of individual nodes. These systems are also susceptible to breakdown resulting from errors in the transmission of neighboring-node information to the other nodes in the network.

5 It is therefore a principal object of the invention to provide a digital network having a relatively low cost per node. Another object of the invention is to provide a network that is completely flexible with regard to location, relocation and addition of network nodes. A further object is to provide a robust network that consumes relatively little power and bandwidth in establishing routing configuration and is also rela-
10 tively immune to problems that cause failures of prior networks.

SUMMARY OF THE INVENTION

A network incorporating the invention is a wireless network that uses an ad-hoc "contour" routing algorithm which allows a message to reach its destination, even when the network topology is incompletely described or rapidly changing. The nodes
15 do not maintain routing tables, but rather cost tables that indicate the "costs" of transmission to other nodes in the network.

For example, assume that node A is separate from node B by several intermediate nodes and that node A is to send a message to node B. Node A cannot reach node B directly. However, it has stored information from previously received mes-
20 sages that node B is four hops away. Node A sends the message to all its neighbors, the message being encapsulated in a network level frame that says, in effect, "forward this message to node B if you can do so in fewer than four hops." All of node A's immediate neighbors receive the message, since the RF transmissions are essentially omnidirectional, but only those nodes that are "closer" to node B will be able to deliver
25 the message in three hops or fewer. Those that are "farther away" would require five hops, for example. Thus, those neighbors that are "on the way" to node B relay the message. In this case the message is encased in a frame that says, in effect, "forward this message to node B if you can do so in two hops or fewer". The process continues until the message reaches node B.

With this process, the intermediate nodes between node A and node B can also keep track of the return path to node A. When originating node A transmits the message, each of its neighbors makes an entry in a cost table to the effect that node A is one hop away. The cost tables in the second tier of intermediate nodes are updated
5 with entries to note that node A is two hops away. This process continues, so that by the time the message arrives at its destination, node B and all the intermediate nodes have retained entries indicating the number of hops to send a message to node A.

As stated above, each of the nodes maintains a table of the number of hops to each of the other nodes in the system. However, this information is not available when
10 the network is installed and it is also unavailable when nodes are added to the network or physically moved to new locations. Accordingly, a flooding algorithm is used when the originating node does not include in its cost table the number of hops to a destination node. Specifically, the originating node sends a *flood* message. This message is relayed once by every node in the network and therefore is guaranteed to eventually
15 find its way to the destination node. The destination node will usually receive replicas of the message over multiple paths. Each replica includes in its frame the number of hops it has traversed since leaving the originating node. Accordingly, the destination node can return a message to the originating node specifying, as the number of hops, the smallest number that was associated with one of the received replicas of the *flood*
20 message. In the same manner, each of the nodes through which the *flood* message passed on the way to the destination node now has information concerning the shortest number of hops to the originating node and can make the appropriate entry in its cost table.

If a node has physically moved so that the cost tables in other nodes are no
25 longer valid, the need to update the cost tables will be ascertained when another node attempts to send a message to that node. The number of hops specified in the message may be exhausted before the message reaches the destination node. The message may therefore not reach the destination node and the originating node will then not receive an acknowledgement of receipt of the message. The originating node can then employ
30 the *flood* algorithm to update the cost tables.

While the foregoing description uses the number of hops on the routing-path as the "cost" criterion, that number is but one example of the cost of transmission. The cost of a hop involving a particular node might be related to other factors, such as the traffic involving that node. In the latter circumstance, a node's cost may change from time to time and this will automatically be reflected in the cost information stored at the other nodes in the network.

It will be apparent from the foregoing that the invention provides a number of important advantages over prior networks. For example, at the physical level, very low-power, localized transmitters can be used in office or home applications. This results in lower hardware costs and low per-node power requirements. Moreover, because of the short range of each RF transmission, the invention provides better utilization of available bandwidth than systems using higher-power transmitters. Additionally, the contour routing technique requires significantly less storage and computation than the Link State Routing and Source Path Routing algorithms.

Furthermore, the contour routing technique supports fully distributed routing algorithms. The network creates its own infrastructure. New nodes may be added simply by introducing them into the system. There is no transmission of network setup and routing information with its consequent overhead and risk of failure from erroneous routing information.

Also, assuming that each node has at least two immediate neighbors, the system is not subject to single-point failures. If a node fails, the network will automatically reconfigure the cost tables as required in order to relay messages from one node to another.

It will be apparent that the advantages of the invention also apply to higher-power networks in which the nodes are more distant from their neighbors. For example a wireless telephone network operating in accordance with the invention might have nodes whose neighbors are hundreds or thousands of meters distant. The individual nodes would be identified by conventional telephone numbers and users would "dial" the numbers of other nodes in placing calls to them. One or more of the nodes

might serve as gateways to other telephone networks and these nodes would respond to conventional prefixes indicating calls to nodes in the other networks.

This arrangement provides a low-cost, self-organizing telephone network which does not require investment in, and maintenance of, a central switch. Moreover, communication with a distant node by multiple hops, as contemplated with the present invention, will generally use a series of low-power transmissions requiring lower overall power than a direct transmission to that node. This conserves battery energy for those nodes that are battery-powered and it also conserves radio-frequency spectrum by largely limiting the range of the transmissions in the area covered by the network.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention description below refers to the accompanying drawings, of which:

Fig. 1 is a diagram of a network incorporating the invention;

Fig. 2 illustrates the format of a network layer level frame used in transmitting messages between the network nodes;

Fig. 3 illustrates the contents of the entries in the cost tables contained in the network nodes;

Fig. 4 is a flow diagram of the operations performed by a network node for transmission of a message; and

Fig. 5 is a flow diagram illustrating the operations performed by a node upon reception of a message.

DETAILED DESCRIPTION OF AN ILLUSTRATIVE EMBODIMENT

As shown in Fig. 1, a network incorporating the invention comprises a plurality of nodes $10_1 \dots 10_N$, each of which communicates with other nodes in the network by means of wireless transmissions. As indicated at the node 10_1 , each of the nodes includes a data originating and/or receiving device 12 coupled to a network interface unit 14. The device 12 can be any of the devices interconnected in a network. For exam-

ple, there may be workstations, file servers, bridges to other networks, etc. Additionally, with the low-cost interface units 14 described herein, the devices 12 can economically be relatively low-cost devices such as condition sensors, controllers and the like which may be deployed in the home as well as in commercial and industrial environments.

Each of the network interface units includes a radio frequency transceiver 16 and a logic unit 18. In the foregoing environments, the transceiver 16 includes a transmitter (not shown) of very low power, e.g. microwatts, and thus can effect communications directly only with immediate neighbors of the node, that is, other nodes that are physically proximate, e.g. within a distance of a few meters. Accordingly, a transmission from a node to most of the other nodes in the network will be a multiple-hop transmission by way of intervening nodes, each of which communicates directly only with its immediate neighbors.

The logic unit 18 has a conventional physical architecture. Thus it includes a microprocessor, a program store and a random access memory. The unit 18 appropriately frames outgoing messages from the device 12 for transmission by the transceiver 16 and processes messages received by the transceiver 16 for delivery to the device 12. The logic unit implements the procedures of the present invention in transmitting, receiving and relaying messages. It may also perform conventional higher-level functions.

Fig. 2 illustrates a network layer frame 22 that can be used by the network nodes operating in accordance with the invention. Each frame includes a *type* field 22a indicating whether the transmission is (1) a point-to-point transmission which is to take the optimum route to the message destination or (2) a flood transmission to be used when the optimum route is unknown. A *destination* field 22b contains the identification of the destination node and an *originator* field 22c identifies the originating node. A *remaining cost* field 22d indicates the remaining allowed cost of the transmission and an *incurred cost* field 22e indicates the cost incurred at any point in the transmission. A *sequence* field 22f contains a sequence number of transmissions from the originating node and, preferably, a *CRC* field 22g contains an error correction bit se-

quence. Finally, the frame includes a *data* field 22h containing the data being transmitted, this data including higher level framing information.

In its random access memory, the logic unit 18 (Fig. 1) stores a cost table. This table contains a set of entries 24 as illustrated in Fig. 3. Each of these entries includes a field 24a containing the identification of a target node, a field 24b specifying the minimum known cost of a transmission to the target node, a field 24c containing a list of the most recent sequence numbers of transmissions received from the target node, and a field 24d indicating the local time at which the entry was last updated.

In Fig. 4, I have illustrated the procedure undertaken by a logic unit 18 (Fig. 1) for the transmission of a message. At step 30, the logic unit searches its cost table for an entry in which the intended recipient of the message is identified in the target ID field 24a. If an entry is not found, the procedure branches at step 32 to a *flood* routine described below. If an entry is found, the logic unit forms a frame 22 at step 33. Specifically, it retrieves from the field 24b in the cost table entry the cost for a transmission to the intended recipient and inserts that value into the field 22d of the frame. It sets the incurred cost to zero to frame 22e. It inserts the node's next sequence number into the frame field 22f, adds the CRC field 22F and data field 22g, and sends the completed frame to the transceiver 16 at step 34 for transmission. The logic unit may then proceed to an acknowledgement loop 36 in which it waits for an acknowledgment from the intended message recipient. If an acknowledgement is received within a predetermined time the transmission process terminates. If it is not, the logic unit branches to the flood transmission procedure. The loop 36 may alternatively be implemented at a higher level protocol layer.

Messages received by a node are processed by the logic unit 18 as illustrated in Fig. 5. At step 40, the logic unit updates the entry in its cost table corresponding to the originating node. Specifically, it updates the cost field in accordance with the incurred cost in the header field 22e; it enters the sequence number of the message in the field 24c in the table entry and updates the time field 24e. At step 42, a logic unit determines whether the node is the destination node of the message. If it is, it exits the routine and passes the message to the next higher protocol layer. If it is not the desti-

nation node, and if the message is not a *flood* message (step 43), it checks its routing table at step 44 for an entry relating to the destination node. If it does not contain such an entry, it exits from the routine. If the cost table does contain an entry, the logic unit proceeds to step 45 where it determines from field 24c of the cost table entry corresponding to the originating node whether the message has been previously received by the node. If it has, the logic unit exits from the routine. If it is not, it proceeds to step 48 in which it ascertains whether the cost of a transmission from its node to the destination node is less than the value contained in the remaining cost field 22d in the message header. If the cost indicated in the corresponding cost table field 24b is greater than the remaining cost, the logic unit exits from the routine. If the cost is less than or equal to the remaining cost, the logic unit proceeds to step 50. Specifically, it decrements the remaining cost in the header field 22d by the amount of the cost of a transmission by its node and increments the value in the incurred cost field 22e by the same amount. At step 52, it then causes its transceiver 16 to retransmit the message with the updated frame 22.

Transmission of a *flood* message is similar to the procedure in Fig. 4. A message frame 22 is formed, with the message type field 22a indicating that the message is a *flood* message. The *remaining cost* field 22d can be set to the maximum value that the transmitting node will incur for a message to the designated recipient. (Alternatively, the field 22d can be set to zero, which indicates to nodes relaying the message that the remaining cost entry is to be ignored). Nodes receiving the message operate in accordance with the routine illustrated in Fig. 5, with the exception that they branch at step 43 and do not check their cost tables for entries relating to the destination node. With the sequence number checked at step 45, a node will not retransmit a flood message more than once.

When a destination node receives a message and transmits an acknowledgment the routing will follow the information contained in the cost tables of the intervening nodes, as updated during the transmission from the originating node to the destination node. When a flood message is received by a destination node, several copies will ordinarily be received from different routes. The destination node updates its cost

table entry relating to the originating node in accordance with the received replica of the message that has the lowest incurred cost and then uses that information in transmissions to the originating node.

With the foregoing arrangement nodes can enter the network or change their
5 locations without the use of setup messages of any kind. That is, entry or relocation is accomplished merely by the transmission of a message, which may be a message of the usual type transmitted by the node in the course of normal operations. The appropriate cost tables in the network are automatically updated to include entries that provide for routing back to that node. Thus, the network is not subject to the overhead of the
10 transmission of routing information. Nor is it subject to breakdown from incorrect transmission of routing information. Furthermore, it is not adversely affected by single-node failure so long as each node has at least two immediate neighbors.

What is claimed is:

CLAIMS

- 1 1. A wireless network comprising a plurality of nodes, each node including:
 - 2 A) A routing table containing a plurality of entries, each entry correspond-
3 ing to another node in the network and containing the cost of transmission to that
4 other node,
 - 5 B) means for forming message frames for transmission of messages to
6 destination nodes, each frame including:
 - 7 1. the identity of the destination node for the message,
 - 8 2. the identification of the originating node,
 - 9 3. the remaining cost of transmission of the message to the desti-
10 nation node, and
 - 11 4. the cost so far incurred in transmission of the message from the
12 originating node to the destination node.
- 1 2. The network defined in claim 1 in which each node further includes means for
2 receiving transmissions, said receiving means including means for:
 - 3 A) if the identity of the destination node contained in the message frame is
4 not the identity of the subject node and
 - 5 B) if the routing table in the receiving node contains an entry correspond-
6 ing to the destination node, that indicates that the cost of the transmission to the desti-
7 nation node is less than the remaining cost value contained in the message frame;
 - 8 1. updating the message frame by incrementing the incurred cost in
9 the message frame by a relay cost associated with the receiving node;
 - 10 2. updating the message frame by decrementing the remaining cost
11 to the message frame by the relay; and
 - 12 3. retransmitting the message.
- 1 3. The system defined in claim 2 in which
 - 2 A) each frame includes a sequence number corresponding to the sequence
3 of messages transmitted from the originating node; and

- 4 B) each routing entry table contains at least the most recent sequence
5 number of messages received by the node from the node to which the table entry cor-
6 responds and
- 7 C) each node includes means for inhibiting retransmission of a message in
8 which the sequence number equals a sequence number contained in the routing table
9 entry corresponding to the node identified in the message frame as the originating
10 node.

1/4




FIG. 1




FIG. 3






FIG. 2

3/4

**FIG. 4**

**FIG. 5**

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 98/15345

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 H04L12/56

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 H04L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	DUBE R ET AL: "SIGNAL STABILITY-BASED ADAPTIVE ROUTING (SSA) FOR AD HOC MOBILE NETWORKS" IEEE PERSONAL COMMUNICATIONS, vol. 4, no. 1, February 1997, pages 36-45, XP000679252 see page 36, right-hand column, line 34 - page 37, right-hand column, line 35 see page 40, right-hand column, line 1 - page 41, line 11	1-3
A	BALASUBRAMANIAN RAJAGOPALAN ET AL: "A NEW RESPONSIVE DISTRIBUTED SHORTEST-PATH ROUTING ALGORITHM*" COMPUTER COMMUNICATIONS REVIEW, vol. 19, no. 4, 1 September 1989, pages 237-246, XP000133127 see the whole document	1

☐ Further documents are listed in the continuation of box C.

☐ Patent family members are listed in annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- "&" document member of the same patent family

Date of the actual completion of the international search

9 November 1998

Date of mailing of the international search report

16/11/1998

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl.
Fax: (+31-70) 340-3016

Authorized officer

Perez Perez, J